



OilSafe

Breather Adapter Kits

Extending fluid life saves money and downtime



Domed Flange Adapter Kit

Domed Flange Adapters provide a low profile yet rugged way to mount a 1" NPT desiccant breather to a hydraulic reservoir. Includes 6-hole ANSI pattern gasket and fasteners for perfect replacement of bayonet flange and vent cap. The beveled surface directs spills and contaminants away from the opening.

(Available in a dark gray colour.)

Height : 0.75 inch (1.9 cm)

Diameter : 3.5 inch (8.89 cm)

Mounting

Connection : ANSI 6-hole pattern flange

Part # : A114DG

Brand : OilSafe



Drum Adapter Kits

Drum Adapter Kits allow breathers to be installed on any storage tank or drum; there's never been a cleaner, more effective way to store, filter and pump lubricants from a drum. Unique design ensures all fluid handling is managed through one adapter. Anodized aluminum adapters have colourized quick connects for pumping oil in and out of drum. Single-port access to the oil reduces contamination as drum remains closed. Off-line filtration units easily connect to adapter without ever disrupting the performance of the breather.

Drum Adapter Kits are available in a dark gray colour and configured with:

- no Quick Connects,
- ISO-B Quick Connects or
- Colourized Quick Connects available in 10 familiar OilSafe colours or silver.

Height: 4.75 inch (12.065 cm)
Diameter: 2.5 inch (6.35 cm)
Mounting
Connection: 2" MNPT
Brand: OilSafe





Drum Adapter Kits

Typical Industries

Automotive

Pulp & Paper

Steel Production/Manufacturing

Food & Beverage

General Manufacturing

Mining/Construction

Power Generation

Petroleum/Chemical Refining

Benefits

Customizable

Seamless connection between your equipment and filtration system

Utilizing a desiccant breather will prevent the ingress of dirt and moisture



Drum Adapter Kits – Part Numbers

No Quick Disconnects

960NQ

Male Disconnects Only

960ISOM - ISO B connects

960BGM - Beige

960BKM – Black

960BLM - Blue

960DGM - Dark Green

960GYM - Dark Gray

960MGM - Mid Green

960ORM - Orange

960RDM - Red

960SLM - Silver

960YLM - Yellow

Male & Female Disconnects

960ISOMF - ISO B connects

960BGMF - Beige

960BKMF - Black

960BLMF - Blue

960DGMF - Dark Green

960GYMF - Dark Gray

960MGMF - Mid Green

960ORMF - Orange

960RDMF - Red

960SLMF - Silver

960YLMF - Yellow

Gearbox Adapter Kit

Gearbox Adapter Kits allow breathers to be installed on any gearbox. Oil can be pumped in or out without opening the gearbox to atmosphere. Offline filtration, oil changes and sampling can be handled through the adapter. They are a faster, simpler and cleaner way to handle gear oils and reduce ingress.

Gearbox Adapter Kits are available in a dark gray colour and configured with:

- no Quick Connects,
- ISO-B Quick Connects or
- Colourized Quick Connects* available in 10 familiar OilSafe colours or silver.

Height : (1", 3/4", 1/2" Adapter) - 3"
Diameter : (1", 3/4" Adapter) - 1.75" (1/2" Adapter) - 1.25"
Mounting
Connection : (1" Adapter) - 1" MNPT (3/4" Adapter) - 3/4" MNPT (1/2" Adapter) - 1/2" MNPT
Brand : OilSafe



**** Managing Machine Reliability ****



Gearbox Adapter Kit

Typical Industries

Automotive

Pulp & Paper

Steel Production/Manufacturing

Food & Beverage

General Manufacturing

Mining/Construction

Power Generation

Petroleum/Chemical Refining

Benefits

Customizable

Seamless connection between your equipment and filtration system

Utilizing a desiccant breather will prevent the ingress of dirt and moisture.



Gearbox Adapter Kit Part Numbers

No Quick Disconnects	
962NQ	
Male Disconnects 1" fit	
<i>962ISOM - ISO B connects</i>	Male & Female Disconnects 1"fit
9621BGM - Beige	<i>962ISOMF - ISO B connects</i>
9621BKM - Black	9621BGMF - Beige
9621BLM - Blue	9621BKMF - Black
9621DGM - Dark Green	9621BLMF - Blue
9621GYM - Dark Gray	9621DGMF - Dark Green
9621MGM - Mid Green	9621GYMF - Dark Gray
9621ORM - Orange	9621MGMF - Mid Green
9621RDM - Red	9621ORMF - Orange
9621SLM - Silver	9621RDMF - Red
9621YLM - Yellow	9621SLMF - Silver
	9621YLMF - Yellow
Male Disconnects 1/2" fit	
<i>96212ISOM - ISO B connects</i>	Male & Female Disconnects 1/2" fit
96212BGM - Beige	<i>96212ISOMF - ISO B connects</i>
96212BKM - Black	96212BGMF - Beige
96212BLM - Blue	96212BKMF - Black
96212DGM - Dark Green	96212BLMF - Blue
96212GYM - Dark Gray	96212DGMF - Dark Green
96212MGM - Mid Green	96212GYMF - Dark Gray
96212ORM - Orange	96212MGMF - Mid Green
96212RDM - Red	96212ORMF - Orange
	96212RDMF - Red

Hydraulic Reservoir Adapter Kit

Hydraulic Reservoir Adapter Kits allow breathers to be installed on any hydraulic fluid tank or reservoir. The patent-pending aluminum adapters have colorized quick connects in two sizes for pumping oil in and out, allowing the system to remain closed at all times, dramatically reducing contamination while improving oil-handling safety. Off-line filtration can also be connected through the adapter without ever disrupting the breather or opening the tank.

Hydraulic Reservoir Adapter Kits are available in a dark gray colour and configured with:

- no Quick Connects,
- ISO-B Quick Connects or
- Colourized Quick Connects* available in 10 familiar OilSafe colours or silver.

Height : 1.875 inch (4.7625 cm)
Diameter : 3.5 inch (8.89 cm)
Mounting
Connection : ANSI 6 hole pattern flange
Brand : OilSafe





Hydraulic Reservoir Adapter Kit

Typical Industries

Automotive

Pulp & Paper

Steel Production/Manufacturing

Food & Beverage

General Manufacturing

Mining/Construction

Power Generation

Petroleum/Chemical Refining

Benefits

Customizable

Seamless connection between your equipment and filtration system

Utilizing a desiccant breather will prevent the ingress of dirt and moisture

Hydraulic Reservoir Adapter Kit Part Numbers

No Quick Disconnects	
961NQ	
Male Disconnects Only	Male & Female Disconnects
<i>961ISOM - ISO B connects</i>	<i>961ISOMF - ISO B connects</i>
961BGM - Beige	961BGMF - Beige
961BKM - Black	961BKMF - Black
961BLM - Blue	961BLMF - Blue
961DGM - Dark Green	961DGMF - Dark Green
961GYM - Dark Gray	961GYMF - Dark Gray
961MGM - Mid Green	961MGMF - Mid Green
961ORM - Orange	961ORMF - Orange
961RDM - Red	961RDMF - Red
961SLM - Silver	961SLMF - Silver
960YLM - Yellow	961YLMF - Yellow

ADAPTER KITS

		Height inches/cm	Diameter inches/cm	Mounting connection	Screws and Gasket	Quick connect pop it style	Sample port model a651	Gauge Port Model A655	Pipe Length
Domed flange adapter (1"NPT breather)		0,8 (1,9)	3,5 (8,9)	Ansi 6-hole pattern flange	Yes	n/a	No	No	n/a
Drum adapter kit		4,8 (12,1)	2,5 (6,4)	2" MNPT	n/a	Oil in (1/2") Oil out (3/4")	Yes	Yes	Oil in 0,5"D x 12"L Oil Out 0,75"D x 32"L
Drum adapter kit		4,8 (12,1)	2,5 (6,4)	2" MNPT	n/a	No	Yes	Yes	Oil in 0,5"D x 12"L Oil Out 0,75"D x 32"L
Hydraulic reservoir adapter kit		1,9 (4,8)	3,5 (8,9)	Ansi 6-hole pattern flange	Yes	Oil in (1/2") Oil out (3/4")	Yes	Yes	0,5"D x 12"L
Hydraulic reservoir adapter kit		1,9 (4,8)	3,5 (8,9)	Ansi 6-hole pattern flange	Yes	No	Yes	Yes	0,5"D x 12"L
Gearbox adapter kit		2,9 (7,3)	1,0 (2,5)	1/2" MNPT	n/a	Oil in (1/2") Oil out (3/4")	Yes	No	n/a
Gearbox adapter kit		2,9 (7,3)	1,0 (2,5)	1/2" MNPT	n/a	No	Yes	No	n/a
Gearbox adapter kit		3,0 (7,6)	1,5 (3,8)	3/4" MNPT	n/a	Oil in (1/2") Oil out (3/4")	Yes	No	n/a
Gearbox adapter kit		3,0 (7,6)	1,5 (3,8)	3/4" MNPT	n/a	No	Yes	No	n/a
Gearbox adapter kit		3,0 (7,6)	1,5 (3,8)	1" MNPT	n/a	Oil in (1/2") Oil out (3/4")	Yes	No	n/a
Gearbox adapter kit		3,0 (7,6)	1,5 (3,8)	1" MNPT	n/a	No	Yes	No	n/a

Colour-coded quick connects

Simplicity, Flexibility, Reliability

The colour-coded, strong, anodized aluminum flat-face quick connectors are easy to use and almost impossible to cross-connect. Purity across your distribution processes and lube storage are thereby guaranteed. The quick connect integrate with a wide range of lubrication management systems and equipment.

Each colour coded, keyed, female colour connector only fits its male matching color.


The **silver Quick Connect** is available as a **universal fit** (not keyed) for all 10 colours.

OilSafe's Quick Connects keep your machinery and fluids lasting longer while maintaining a safe and efficient work environment. These zero-leak quick connects eliminate wastes and spills throughout your facility.



Colour Coded Quick Connects



 **OilSafe** *Quick Connects keep your machinery and fluids lasting longer*

Contact Information:

Enluse B.V.

Dijnselburgerlaan 7
3705 LP ZEIST - Netherlands

Office :

+31 (0) 765 781 280

info@enluse.com

www.enluse.com

Direct :

Toon van Grunderbeeck

+32 (0) 476 23 83 78

toonvg@enluse.com

UK:

Andrew Laing

UK Contact Tel: +44 7393 429957

andrew.laing@enluse.co.uk