

G-LOCK

QUICK GREASE GUN COUPLER



Hydraulic Safety-Coupler (2 types)

- With hardened 4-jaws made of tool steel
- With high-performance hydraulic-gasket
- With integrated linear-swivel
- With internal valve and shock absorber
- Uncoupling over 600 bar is possible
- No spurt / mess when uncoupling
- Outer diameter according to DIN

1. ME-0141087032: G-Lock, Quick Grease Gun coupler, Quick Disconnect, M10x1, 32 mm

- With hardened 4-jaws made of tool steel
- With high performance hydraulic gasket
- Uncoupling over 600 bar is possible
- Swiveling joint with thread M 10x1 mm
- Coupler length: 32 mm

2. ME-0141087081: G-Lock, Quick Grease Gun coupler, Quick Disconnect, M10x1, 81 mm

- With hardened 4-jaws made of tool steel
- With high performance hydraulic gasket
- Uncoupling over 600 bar is possible
- Swiveling joint with thread M 10x1 mm
- Coupler length: 81 mm



32 mm

ME-0141087032



81 mm

ME-0141087081

The advantages of the coupler

1. Simple activation

- To activate the coupler you only have to press the lever with the thumb and insert it on the grease gun. The hardened 4-jaws maintain the coupler firmly inserted.



2. Simple release

- After you have finished the greasing process, you have to press the lever with the thumb to pull out the coupler from the grease gun.



3. Free hands

- Once you have activated the coupler, it remains firmly inserted so there is no need to keep it fixed. Its extreme stability allows you to complete the operation with free hands.

4. Universality

- Its special design allows to use it with all the grease guns configurations: SAE, DIN, BS, etc.

