

# 55 L Mobile Fluid Tank with Integrated Battery-Powered Pump



LT-LCBOPUE

## Product Overview

The 55 L Mobile Fluid Tank is a compact, portable dispensing solution designed for safe and efficient handling of oils, hydraulic fluids and other compatible lubricants. Equipped with a high-performance battery-powered pump, the unit delivers clean, controlled dispensing in workshops, agricultural environments, fleet maintenance operations and mobile service applications.

## Key Features

- 55 L fluid capacity for convenient on-site dispensing
- Integrated battery-powered pump for cordless, reliable operation
- Multi-fluid compatible, suitable for oils, hydraulic fluids, lubricants and gear oils
- Portable and manoeuvrable for workshop and field servicing
- Robust industrial-grade tank designed for daily professional use

- Low-contamination design to protect fluid integrity
- Optional desiccant breather for enhanced moisture and particle protection
- Optional digital meter for precise measurement and controlled dispensing

## **Technical Specifications**

### **Tank Capacity:**

- 55 litres

### **Pump Type:**

- Battery-powered pump
- Suitable for low to medium-viscosity fluids

### **Fluid Compatibility:**

- Engine oil
- Hydraulic oil
- Gear oil
- Transmission fluids
- Light lubricants

### **Construction:**

- High-density industrial-grade materials
- Impact-resistant housing
- Chemical-resistant seals and fittings

### **Mobility:**

- Integrated carry/handling system
- Compact footprint for easy storage and transport

### **Dispensing Performance:**

- Clean, controlled fluid delivery
- Reduced spill risk
- Optional digital meter for high-accuracy output

### Protection Options:

- Desiccant breather: prevents moisture ingress and contamination
- Digital meter: displays real-time flow and total dispensed volume

Pump	18 V battery operated oil pump BOP60/205L
Hose + gun	1.2 m PVC reinforced, anti drip gun
Breather	Desiccant breather orange - green
Dimensions	480 x 350 x 900 mm
Material	Roto molded inert industrial HDPE, translucent
Weight Empty	15 kg , including pump, breather
Content	55 liter
Options	Digital Oil Meter, other pumps,...

### Benefits

- Improved workflow efficiency: eliminates manual pouring and heavy drum handling
- Cleaner and safer maintenance: reduces contamination and spill hazards
- Precise fluid management: optional digital meter minimises waste
- Enhanced lubricant quality: desiccant breather option keeps fluids clean and dry
- Ideal for mobile operations: perfect for field service and on-site maintenance
- Cost-effective maintenance: consistent output reduces product overuse

### Typical Applications

- Automotive workshops
- Agricultural machinery maintenance
- Construction equipment service
- Industrial plant maintenance
- Fleet depots and mobile service vans

## Flow Rate

Type of Oil	BOP 20L	BOP 60/205L
Engine Oil	3,5 LPM	4,5 LPM
High Vis Oil	Up to 2 LPM	Up to 2,4 LPM
ATF	Up to 4,5 LPM	Up to 6 LPM
Coolant	5,8 LPM	6,2 LPM
Compatible Fluids	<i>Suitable for engine oil gear hydraulic oil (oils up to SAE140 viscosity), automatic transmission fluids (ATF) and engine coolant</i>	

## Safety & Handling

- Always use approved fluids compatible with the pump system.
- Store the unit on a stable, level surface.
- Keep battery components dry and protected during operation and transport.
- Follow all local regulations regarding lubricant storage and environmental safety.

## Warranty

Standard manufacturer's warranty applies.