

SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR4 SYNTHETIC 2T ENGINE OIL



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : VROOAM VR4 SYNTHETIC 2T ENGINE OIL
 Product code : 63684
 Type of product : Lubricants
 Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use.
 Use of the substance/mixture : Engine oil

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

VROOAM Powersports Lubricants INT. B.V.
 Aventurijn 300
 3316 LB Dordrecht (NL)
 0031 (0) 78 750 1632
 www.vrooam-lubricants.com
 info@vrooam-lubricants.com

· Further information obtainable from: Product Safety Department

1.4. Emergency telephone number: 0031 (0) 78 750 16 32 (9 AM to 5 PM, Monday to Friday)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]
 Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.
 EUH208 - Contains reaction mass of: dicalcium (bis(2-hydroxy-5-tetrapropenylphenylmethyl) methylamine)dihydroxide, tri-calcium (tris(2-hydroxy-5-tetrapropenylphenylmethyl) methylamine)tri-hydroxide, poly[calcium ((2-hydroxy-5-tetrapropenyl- phenylmethyl)methylamine)hydroxide].
 May produce an allergic reaction.

2.3. Other hazards

No additional information available

SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR4 SYNTHETIC 2T ENGINE OIL



SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Highly refined mineral oils and additives.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(EC-No.) 926-141-6 (REACH-no) 01-2119456620-43	20 -25	Asp. Tox. 1, H304
Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivatives	(CAS-No.) 84605-20-9 (EC-No.) 617-593-2	1 - 5	Aquatic Chronic 4, H413

Comments : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Full text of H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
 First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
 First-aid measures after skin contact : Wash skin with plenty of water.
 First-aid measures after eye contact : Rinse eyes with water as a precaution.
 First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : No additional information available. Not expected to present a significant hazard under anticipated conditions of normal use.
 Symptoms/effects after ingestion : May result in aspiration into the lungs, causing chemical pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
 Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.
 Hazardous decomposition products in case of fire : Toxic fumes may be released. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR4 SYNTHETIC 2T ENGINE OIL



SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep in a cool, well-ventilated place away from heat.

Storage temperature : 0 - 40 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VROOAM VR4 SYNTHETIC 2T ENGINE OIL	
EU - Occupational Exposure Limits	
Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended	5 mg/m ³ - ACGIH TLV (inhalable fraction).

SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR4 SYNTHETIC 2T ENGINE OIL



8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Materials for protective clothing : Wear suitable protective clothing

Hand protection : Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	=> 0.35	EN ISO 374	

Eye protection : Safety glasses

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -45 °C - ASTM D5950 (pour point)
Boiling point	: No data available
Flash point	: 78 °C - ASTM D92 (COC)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,872 kg/l (15 °C) - ASTM D4052
Solubility	: Water : Practically not miscible.
Log Pow	: No data available
Viscosity, kinematic	: 70,5 mm ² /s (40 °C) - ASTM D7279
Viscosity, dynamic	: No data available
Explosive properties	: Presents no particular fire or explosion hazard.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 0 %

SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR4 SYNTHETIC 2T ENGINE OIL



SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition

No decomposition if stored normally.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401 method)
LD50 dermal rabbit	> 5000 mg/kg bodyweight 24h - (OECD 402 method)
LC50 inhalation rat (mg/l)	> 5000 mg/m ³ 8h - vapours (OECD 403 method)

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

VROOAM VR4 SYNTHETIC 2T ENGINE OIL	
Viscosity, kinematic	70,5 mm ² /s (40 °C) - ASTM D7279

SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR4 SYNTHETIC 2T ENGINE OIL



SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
LC50 fish 1	> 1000 mg/l (OECD 203 method)
EC50 Daphnia 1	> 1000 mg/l (OECD 202 method)
EC50 72h algae (1)	> 1000 mg/l (OECD 201 method)
NOEC chronic crustacea	1,22 g/l (21d)
NOEC chronic algae	1000 mg/l (OECD 201 method)

12.2. Persistence and degradability

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Biodegradation	69 % (28d) (OECD 301F method)

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not allow into drains or water courses. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

European List of Waste (LoW) code : 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils

RUBRIEK 14: Informatie met betrekking tot het vervoer

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				

SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR4 SYNTHETIC 2T ENGINE OIL



Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport	Not applicable
Transport by sea	Not applicable
Air transport	Not applicable
Inland waterway transport	Not applicable
Rail transport	Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants.

VOC content : 0 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level

SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR4 SYNTHETIC 2T ENGINE OIL



NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:	
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains reaction mass of: dicalcium (bis(2-hydroxy-5-tetrapropenylphenylmethyl) methylamine)dihydroxide, tri-calcium (tris(2-hydroxy-5-tetrapropenylphenylmethyl) methylamine)tri-hydroxide, poly[calcium ((2-hydroxy-5-tetra- propenylphenylmethyl) methylamine)hydroxide]. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.