

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4l



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name : VROOAM WHITE CHAIN LUBE 0,4l  
Product code : 63905

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture Grease

### 1.3. Details of the supplier of the safety data sheet

VROOAM Powersports Lubricants INT. B.V.  
Aventurijn 300  
3316 LB Dordrecht (NL)  
0031 (0) 78 750 1632  
[www.vrooam-lubricants.com](http://www.vrooam-lubricants.com)  
[info@vrooam-lubricants.com](mailto:info@vrooam-lubricants.com)

· Further information obtainable from: Product Safety Department

1.4. Emergency telephone number: 0031 (0) 78 750 16 32 (9 AM to 5 PM, Monday to Friday)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]



GHS02 flame

Aerosol 1 : H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 : H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 : H315 Causes skin irritation.  
STOT SE 3 : H336 May cause drowsiness or dizziness.  
Asp. Tox. 1 : H304 May be fatal if swallowed and enters airways.

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4I



Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS09

Signal word (CLP) : Danger

Hazard-determining components of labelling:

Pentane Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane. Distillates (petroleum), hydrotreated light.

Hazard statements (CLP) : H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P301+P310 IF SWALLOWED: Immediately call a doctor.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/ regional/ national/ international regulations.

## 2.3. Other hazards

### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Description: Active substance with propellant

### 3.2. Mixtures

| Dangerous components   |   |         |
|--|---|---------|
| CAS: 109-66-0<br>EINECS: 203-692-4<br>Reg.nr.: 01-2119459286-3 | Pentane<br>Flam. Liq. 1, H224; Asp. Tox. 1, H304; Aquatic Chronic 2, H411;<br>STOT SE 3, H336   | 25-<50% |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Reg.nr.: 01-2119474691-3 | butane (containing < 0.1% butadiene (203-450-8))<br>Flam. Gas 1, H220; Press. Gas (Comp.), H280 | 10-<25% |

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4l



| Dangerous components   |  |          |
|--|--|----------|
| CAS: 92128-66-0<br>EC number: 921-024-6<br>Reg.nr.: 01-2119475514-35 | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane<br>Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411;<br>Skin Irrit. 2, H315; STOT SE 3, H336 | 10-<25%  |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Reg.nr.: 01-2119486944-21       | propane<br>Flam. Gas 1, H220; Press. Gas (Comp.), H280   | 10-<25%  |
| CAS: 64742-47-8<br>EC number: 926-141-6<br>Reg.nr.: 01-2119456620-43 | Distillates (petroleum), hydrotreated light<br>Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336  | 2.5-<10% |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Reg.nr.: 01-2119485395-27       | isobutane (containing < 0,1 % butadiene (203-450-8))<br>Flam. Gas 1, H220; Press. Gas (Comp.), H280  | 2.5-<10% |

Additional information:

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

After inhalation : Supply fresh air; consult doctor in case of complaints.  
After skin contact : Generally the product does not irritate the skin.  
After eye contact : Rinse opened eye for several minutes under running water.  
After swallowing : Do not induce vomiting; call for medical help immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing agents** : Water haze  
Fire-extinguishing powder  
Carbon dioxide  
Alcohol resistant foam

**For safety reasons unsuitable extinguishing agents:** Water with full jet

### 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

### 5.3 Advice for firefighters

Protective equipment: Mount respiratory protective device.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4I



## 6.2. Environmental precautions

Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

## 6.3. Methods and material for containment and cleaning up

Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

## 6.4. Reference to other sections

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

#### Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage

Requirements to be met by storerooms and receptacles : Store in a cool location.  
: Observe official regulations on storing packagings with pressurised containers.

#### Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

#### Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

### 8.1. Control parameters

| Ingredients with limit values that require monitoring at the workplace: |   |
|---|---|
| <b>109-66-0 Pentane</b>   |   |
| WEL   | Long-term value: 1800 mg/m <sup>3</sup> , 600 ppm |
| <b>106-97-8 butane (containing &lt; 0.1% butadiene (203-450-8))</b>     |   |

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4I



|  |   |
|--|---|
| WEL  | Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm<br>Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm<br>Carc (if more than 0.1% of buta-1.3-diene) |
| <b>74-98-6 propane</b>   |   |
| WEL  | Long-term value: 1800 mg/m <sup>3</sup>   |
| <b>75-28-5 isobutane (containing &lt; 0,1 % butadiene (203-450-8))</b> |   |
| WEL  | Short-term value: 2400 mg/m <sup>3</sup><br>Long-term value: 1900 mg/m <sup>3</sup>   |

| DNELs  |                         |   |
|--|-------------------------|---|
| <b>109-66-0 Pentane</b>  |                         |   |
| Oral   | DNEL Long term-systemic | 214 mg/kg bw/day (Consumer)   |
| Dermal   | DNEL Long term-systemic | 214 mg/kg bw/day (Consumer)<br>432 mg/kg bw/day (Worker)            |
| Inhalative   | DNEL Long term-systemic | 643 mg/m <sup>3</sup> (Consumer)<br>3000 mg/m <sup>3</sup> (Worker) |
| <b>92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> |                         |   |
| Oral   | DNEL Long term-systemic | 699 mg/kg bw/day (Consumer)   |
| Dermal   | DNEL Long term-systemic | 699 mg/kg bw/day (Consumer)<br>773 mg/kg bw/day (Worker)            |
| Inhalative   | DNEL Long term-systemic | 608 mg/m <sup>3</sup> (Consumer)<br>2035 mg/m <sup>3</sup> (Worker) |

**Additional information:** The lists valid during the making were used as basis.

## 8.2. Exposure controls

### Personal protective equipment:

#### General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

#### Respiratory protection:

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

#### Protection of hands:

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: <sup>3</sup> 0.5 mm

#### Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4I



recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye protection:

Safety glasses



Tightly sealed goggles

Body protection: Use protective suit. (EN-13034/6)

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### General Information

##### Appearance:

Form : Aerosol  
Colour : According to product specification

Odour : characteristic.  
Odour threshold : Not determined.  
pH -value : Not determined

##### Change in condition:

Melting point : Undetermined  
Initial boiling point and boiling range : -44.5 °C

Flash point : -97 °C  
Flammability (solid, gas) : Not applicable.  
Auto-ignition temperature : Product is not self igniting.  
Explosive properties : Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.  
Not determined.

##### Explosion limits:

Lower : 0.7 Vol %  
Upper : 10.9 Vol %

Vapour pressure at 20 °C : 8300 hPa  
Density at 20 °C : 0.654 g/cm<sup>3</sup>  
Relative density : Not determined.  
Vapour density : Not determined.  
Evaporation rate : Not applicable.

##### Solubility in / Miscibility with

Water : Not miscible or difficult to mix.

Partition coefficient: n-octanol/water : Not determined.

##### Viscosity:

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4I



Dynamic : Not determined.  
Kinematic : Not determined.

**Solvent content:**  
Organic solvents : 84.2 %  
Solids content : 4.9 %

## 9.2 Other information

No further relevant information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No further relevant information available

### 10.2. Chemical stability

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known.

### 10.4. Conditions to avoid

No further relevant information available.

### 10.5. Incompatible materials

No further relevant information available.

### 10.6. Hazardous decomposition products

No dangerous decomposition products known.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Acute toxicity** : Based on available data, the classification criteria are not met.

| LD/LC50 values relevant for classification:                                  |         |                      |
|--|---------|----------------------|
| 92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane |         |                      |
| Oral   | LD50    | >5840 mg/kg (rat)    |
| Dermal   | LD50    | >2920 mg/kg (rabbit) |
| Inhalative   | LC50/4h | >25 mg/l (rat)       |
| 64742-47-8 Distillates (petroleum), hydrotreated light                       |         |                      |
| Oral   | LD50    | >5000 mg/kg (rat)    |
| Dermal   | LD50    | >5000 mg/kg (rabbit) |
| Inhalative   | LC50/8h | >5000 mg/kg (rat)    |

### Primary irritant effect:

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Based on available data, the classification criteria are not met.  
Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4I



|                        |   |
|------------------------|---|
| Germ cell mutagenicity | : Based on available data, the classification criteria are not met. |
| Carcinogenicity        | : Based on available data, the classification criteria are not met. |
| Reproductive toxicity  | : Based on available data, the classification criteria are not met. |
| STOT-single exposure   | : May cause drowsiness or dizziness.                                |
| STOT-repeated exposure | : Based on available data, the classification criteria are not met. |
| Aspiration hazard      | : May be fatal if swallowed and enters airways.                     |

## SECTION 12: Ecological information

### 12.1 Toxicity

· Aquatic toxicity:

|  |   |
|--|---|
| <b>109-66-0 Pentane</b>  |   |
| NOELR (72h)  | 7.51 mg/l (Pseudokirchneriella subcapitata)   |
| EC50 (72h)   | 10.7 mg/l (Pseudokirchneriella subcapitata)   |
| LC50/96h   | 4.26 mg/l (Oncorhynchus mykiss (96h))         |
| EC50/48h   | 2.7 mg/l (Daphnia magna)                      |
| <b>92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> |   |
| NOELR (72h)  | 3 mg/l (Pseudokirchneriella subcapitata)      |
| EL50(48h)  | 3 mg/l (Daphnia magna)                        |
| EL50 (72h)   | 30-100 mg/l (Pseudokirchneriella subcapitata) |
| LL50 (96h)   | 11.4 mg/l (Oncorhynchus mykiss (96h))         |
| NOEC (21 days)   | 0.17 mg/l (Daphnia magna)                     |
| LOEC (21 days)   | 0.32 mg/l (Daphnia magna)                     |
| <b>64742-47-8 Distillates (petroleum), hydrotreated light</b>                          |   |
| ELO (48h)  | 1000 mg/l (Daphnia magna)                     |
| ELO(72h)   | 1000 mg/l (Pseudokirchneriella subcapitata)   |
| LLO(96h)   | 1000 mg/l (Oncorhynchus mykiss (96h))         |

### 12.2 Persistence and degradability

No further relevant information available.

### 12.3 Bioaccumulative potential

No further relevant information available.

### 12.4 Mobility in soil

No further relevant information available.

Ecotoxicological effects:

Remark

: Toxic for fish

Additional ecological information:

General notes

: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

### 12.5 Results of PBT and vPvB assessment

PBT

: Not applicable.

vPvB

: Not applicable.

### 12.6 Other adverse effects

No further relevant information available.

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4l



## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Recommendation : Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| European waste catalogue |   |
|--------------------------|---|
| HP3                      | Flammable   |
| HP5                      | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity |
| HP14                     | Ecotoxic  |

Uncleaned packaging:  
Recommendation : Disposal must be made according to official regulations.

## RUBRIEK 14: Informatie met betrekking tot het vervoer

|   |   |
|---|---|
| <b>14.1 UN-Number</b>   |   |
| ADR, ADN, IMDG, IATA  | : UN1950  |
| <b>14.2 UN proper shipping name</b>   |   |
| ADR, ADN  | : UN1950 AEROSOLS   |
| IMDG  | : AEROSOLS (PENTANES, Hydrocarbons, C6-C7, nalkanes, isoalkanes, cyclics, <5% n-hexane), MARINE POLLUTANT |
| IATA  | : AEROSOLS, flammable   |
| <b>14.3 Transport hazard class(es)</b>  |   |
| <b>ADR</b>  |   |
|  |   |
| Class   | : 2 5F Gases.   |
| Label   | : 2.1   |
| <b>ADN</b>  |   |
| ADN/R Class   | : 2 5F  |
| <b>IMDG</b>   |   |
|  |   |
| Class   | : 2.1   |
| Label   | : 2.1   |
| <b>IATA</b>   |   |
|  |   |
| Class   | : 2.1   |
| Label   | : 2.1   |
| <b>14.4 Packing group</b>   |   |
| ADR, IMDG, IATA   | : Void  |

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4I



|  |  |
|--|--|
| <b>14.5 Environmental hazards:</b>   |  |
| Product contains environmentally hazardous substances                          | : Pentane  |
| Marine pollutant   | : Yes  |
| Special marking (ADR)  | : Symbol (fish and tree)<br>: Symbol (fish and tree)   |
| <b>14.6 Special precautions for user</b>                                       |  |
| Warning  | : Gases.   |
| Danger code (Kemler)   | : -  |
| · EMS Number   | : F-D,S-U  |
| · Segregation Code   | : SG69 For AEROSOLS with a maximum capacity of 1 litre:<br>Stowage Code SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.<br>Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.<br>For AEROSOLS with a capacity above 1 litre:<br>Segregation as for the appropriate subdivision of class 2.<br>For WASTE AEROSOLS:<br>Segregation as for the appropriate subdivision of class 2. |
| <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b> |  |
| Not applicable.  |  |
| Transport/Additional information:  |  |
| ADR  |  |
| Limited quantities (LQ)  | : 1L   |
| Excepted quantities (EQ) Code  | : E0   |
|  | Not permitted as Excepted Quantity   |
| Transport category   | : 2  |
| Tunnel restriction code  | : D  |
| IMDG   |  |
| Limited quantities (LQ)  | : 1L   |
| Excepted quantities (EQ) Code  | : E0   |
|  | Not permitted as Excepted Quantity   |
| UN "Model Regulation"  | : UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS   |

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category**

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4I



## National regulations:

| Class | Share in % |
|-------|------------|
| NK    | 75-<100    |

VOC-CH 84.20 %

VOC-EU 550.7 g/l

Danish MAL Code 5-3

## 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Relevant phrases

- H220 Extremely flammable gas.
- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Research & Development

Contact: VROOAM Lubricants

### Abbreviations and acronyms:

|                    |  |
|--------------------|--|
| RID                | : Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) |
| ICAO               | : International Civil Aviation Organisation  |
| ADR                | : Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)                  |
| IMDG               | : International Maritime Code for Dangerous Goods  |
| IATA               | : International Air Transport Association  |
| GHS                | : Globally Harmonised System of Classification and Labelling of Chemicals  |
| EINECS             | : European Inventory of Existing Commercial Chemical Substances  |
| ELINCS             | : European List of Notified Chemical Substances  |
| CAS                | : Chemical Abstracts Service (division of the American Chemical Society)   |
| MAL-Code           | : Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)   |
| DNEL               | : Derived No-Effect Level (REACH)  |
| LC50               | : Lethal concentration, 50 percent   |
| LD50               | : Lethal dose, 50 percent  |
| PBT                | : Persistent, Bioaccumulative and Toxic  |
| vPvB               | : very Persistent and very Bioaccumulative   |
| Flam. Gas 1        | : Flammable gases – Category 1   |
| Aerosol 1          | : Aerosols – Category 1  |
| Press. Gas (Comp.) | : Gases under pressure – Compressed gas  |
| Flam. Liq. 1       | : Flammable liquids – Category 1   |
| Flam. Liq. 2       | : Flammable liquids – Category 2   |

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM WHITE CHAIN LUBE 0,4l



|                   |  |
|-------------------|--|
| Flam. Liq. 3      | : Flammable liquids – Category 3   |
| Skin Irrit. 2     | : Skin corrosion/irritation – Category 2                                       |
| STOT SE 3         | : Specific target organ toxicity (single exposure) – Category 3                |
| Asp. Tox. 1       | : Aspiration hazard – Category 1   |
| Aquatic Chronic 2 | : Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 |

\* Data compared to the previous version altered. \*