

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
 Product name : VROOAM MPL MULTIPURPOSE LUBRICANT  
 Product code : 63924  
 Vaporizer : Aerosol  
 UFI : 1QEV-46R7-HX58-1MAK

### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

#### 1.2.1. Relevant identified uses

No additional information available

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

VROOAM Powersports Lubricants INT. B.V.  
 Aventurijn 300  
 3316 LB Dordrecht (NL)  
 0031 (0) 78 750 1632  
[www.vrooam-lubricants.com](http://www.vrooam-lubricants.com)  
[info@vrooam-lubricants.com](mailto:info@vrooam-lubricants.com)

· Further information obtainable from: Product Safety Department

1.4. Emergency telephone number: 0031 (0) 78 750 16 32 (9 AM to 5 PM, Monday to Friday)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Aerosol, Category 1 H222;H229  
 Specific target organ toxicity – Single exposure, Category 3, H336  
 Narcosis  
 Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness.

### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP)

: Danger

Contains

: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Precautionary statements (CLP) :	H229 - Pressurised container: May burst if heated. H336 - May cause drowsiness or dizziness. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 - Do not pierce or burn, even after use. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
EUH-statements :	EUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
2-butoxyethanol (111-76-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
butane (106-97-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane substance with national workplace exposure limit(s) (AT, BE, BG, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LV, PL, PT, SI, SK)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0	$\geq 25 - < 50$	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258-33	$\geq 25 - < 50$	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Propane substance with national workplace exposure limit(s) (AT, BE, BG, DE, DK, EE, ES, FI, GR, LV, PL, RO, SI)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5	≥ 10 – < 25	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
2-butoxyethanol substance with national workplace exposure limit(s) (BE, FR, GB, NL); substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108-36	≥ 0,1 – < 1	Acute Tox. 3 (Inhalation), H331 (ATE=3 mg/l) Acute Tox. 4 (Oral), H302 (ATE=1200 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Irrit. 2, H319

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.  
Full text of H- and EUH-statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.  
Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.  
Symptoms/effects after eye contact : None under normal conditions.  
Symptoms/effects after ingestion : None under normal conditions.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Packaging materials : Store always product in container of same material as original container.

Storage class (LGK, TRGS 510) : LGK 2B - Aerosol dispensers and lighters

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



## 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

2-butoxyethanol (111-76-2)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	98 mg/m <sup>3</sup>
	20 ppm
IOEL STEL	246 mg/m <sup>3</sup>
	50 ppm
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	98 mg/m <sup>3</sup>
	20 ppm
OEL STEL	246 mg/m <sup>3</sup>
	50 ppm
<b>France - Occupational Exposure Limits</b>	
VME (OEL TWA)	49 mg/m <sup>3</sup>
	10 ppm
VLE (OEL C/STEL)	246 mg/m <sup>3</sup>
	50 ppm
<b>Netherlands - Occupational Exposure Limits</b>	
TGG-8u (OEL TWA)	100 mg/m <sup>3</sup>
	20,4 ppm
TGG-15min (OEL STEL)	246 mg/m <sup>3</sup>
	50 ppm
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA)	123 mg/m <sup>3</sup>
	25 ppm
WEL STEL (OEL STEL)	246 mg/m <sup>3</sup>
	50 ppm

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	20 ppm
<b>butane (106-97-8)</b>	
Austria - Occupational Exposure Limits	
Local name	Butan (beide Isomeren): n-Butan (R 600)
MAK (OEL TWA)	1900 mg/m <sup>3</sup>
	800 ppm
MAK (OEL STEL)	3800 mg/m <sup>3</sup> (3x 60(Mow) min)
	1600 ppm (3x 60(Mow) min)
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Butane, tous isomères: n-butane # Butaan, alle isomeren: n-butaan
OEL STEL	2370 mg/m <sup>3</sup>
<b>butane (106-97-8)</b>	
	980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	n-Бутан
OEL TWA	1900 mg/m <sup>3</sup>
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Butan
GVI (OEL TWA)	1450 mg/m <sup>3</sup>
	600 ppm
KGV I (OEL STEL)	1810 mg/m <sup>3</sup>
	750 ppm
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граниčnim vrijednostima izloženosti i biološkim граниčnim vrijednostima (NN 1/2021)
Denmark - Occupational Exposure Limits	

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Local name	n-Butan
OEL TWA	1200 mg/m <sup>3</sup>
	500 ppm
Regulatory reference	BEK nr 2203 af 29. november 2021
<b>Estonia - Occupational Exposure Limits</b>	
Local name	n-butaan
OEL TWA	1500 mg/m <sup>3</sup>
	800 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
<b>Finland - Occupational Exposure Limits</b>	
Local name	n-Butaani
HTP (OEL TWA)	1900 mg/m <sup>3</sup>
	800 ppm
HTP (OEL STEL)	2400 mg/m <sup>3</sup>
	1000 ppm
Remark	Happea syrjäyttämällä tukahduttavat kaasut.
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	n-Butane
VME (OEL TWA)	1900 mg/m <sup>3</sup>
	800 ppm
Remark	Valeurs recommandées/admises

<b>butane (106-97-8)</b>	
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA)	2400 mg/m <sup>3</sup>
	1000 ppm
Peak exposure limitation factor	4(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission)
Regulatory reference	TRGS900

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Greece - Occupational Exposure Limits	
Local name	Βουτάνιο
OEL TWA	2350 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	n-BUTÁN
AK (OEL TWA)	2350 mg/m <sup>3</sup>
CK (OEL STEL)	9400 mg/m <sup>3</sup>
Remark	N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Butane, all isomers: Butane
OEL STEL	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
Local name	Butāns (kas satur vairāk nekā 0,1 % butadiēna)
OEL TWA	300 mg/m <sup>3</sup>
Remark	Carc. 1A; Muta. 1B
Regulatory reference	Ministru kabineta 2008. gada 29. septembra noteikumi Nr. 803 (Grozījumi Ministru kabineta 2020. gada 7. janvārī noteikumiem Nr. 10).
Poland - Occupational Exposure Limits	
Local name	Butan (n-butan)
NDS (OEL TWA)	1900 mg/m <sup>3</sup>
NDSch (OEL STEL)	3000 mg/m <sup>3</sup>
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	Butano, todos os isómeros
OEL STEL	1000 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014



# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



butane (106-97-8)	
<b>Slovakia - Occupational Exposure Limits</b>	
Local name	Bután s obsahom ≥ 0,1% butadiénu (n-bután)
NPHV (OEL TWA)	2400 mg/m <sup>3</sup> (TSH)
	1000 ppm (TSH)
Remark	Kategória karcinogénov 1A – Dokázaný karcinogén pre ľudí
Regulatory reference	Nariadenie vlády č. 356/2006 Z. z. (235/2020 Z. z.)
<b>Slovenia - Occupational Exposure Limits</b>	
Local name	butan
OEL TWA	2400 mg/m <sup>3</sup>
	1000 ppm
OEL STEL	9600 mg/m <sup>3</sup>
	4000 ppm
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
<b>Spain - Occupational Exposure Limits</b>	
Local name	Butano
VLA-ED (OEL TWA)	1000 ppm Hidrocarburos alifáticos alcanos (C1 – C4) y sus mezclas, gases (Butano; Etano; Metano; Propano)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butane
WEL TWA (OEL TWA)	1450 mg/m <sup>3</sup>
	600 ppm
WEL STEL (OEL STEL)	1810 mg/m <sup>3</sup>
	750 ppm
Remark	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>Iceland - Occupational Exposure Limits</b>	
Local name	n-Bútan
OEL TWA	1200 mg/m <sup>3</sup>
	500 ppm

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
<b>Norway - Occupational Exposure Limits</b>	
Local name	Butan
Grænseverdi (OEL TWA)	600 mg/m <sup>3</sup>
	250 ppm
Regulatory reference	FOR-2021-06-28-2248

<b>butane (106-97-8)</b>	
<b>North Macedonia - Occupational Exposure Limits</b>	
Local name	Бутан
OEL TWA	2400 mg/m <sup>3</sup>
	1000 ppm
KTV	4
Short time value [mg/m <sup>3</sup> ]	9600 mg/m <sup>3</sup>
Short time value [ppm]	4000 ppm
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m <sup>3</sup> или во ml/m <sup>3</sup> (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	n-Butane / n-Butan
MAK (OEL TWA)	1900 mg/m <sup>3</sup>
	800 ppm
KZGW (OEL STEL)	7600 mg/m <sup>3</sup>
	3200 ppm
Critical toxicity	SNC / ZNS

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Regulatory reference	www.suva.ch, 28.03.2022
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Butane
ACGIH OEL STEL	1000 ppm
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2022
<b>propane (74-98-6)</b>	
<b>Austria - Occupational Exposure Limits</b>	
Local name	Propan (R 290)
MAK (OEL TWA)	1800 mg/m <sup>3</sup>
	1000 ppm
MAK (OEL STEL)	3600 mg/m <sup>3</sup> (3x 60(Mow) min)
	2000 ppm (3x 60(Mow) min)
Regulatory reference	BGBI. II Nr. 156/2021
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)
<b>propane (74-98-6)</b>	
OEL TWA	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	Пропан
OEL TWA	1800 mg/m <sup>3</sup>
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Propan (Flaskegas)
OEL TWA	1800 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	BEK nr 2203 af 29. november 2021
<b>Estonia - Occupational Exposure Limits</b>	

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Local name	Propaan
OEL TWA	1800 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
<b>Finland - Occupational Exposure Limits</b>	
Local name	Propaani
HTP (OEL TWA)	1500 mg/m <sup>3</sup>
	800 ppm
HTP (OEL STEL)	2000 mg/m <sup>3</sup>
	1100 ppm
Remark	Happea syrjäyttämällä tukahduttavat kaasut.
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA)	1800 mg/m <sup>3</sup>
	1000 ppm
Peak exposure limitation factor	4(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission)
Regulatory reference	TRGS900
<b>Greece - Occupational Exposure Limits</b>	
Local name	Προπάνιο
OEL TWA	1800 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους

## propane (74-98-6)

### Ireland - Occupational Exposure Limits

Local name	Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane
Remark	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)
Regulatory reference	Chemical Agents Code of Practice 2021

### Latvia - Occupational Exposure Limits

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Local name	Propāns
OEL TWA	1800 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2015. gada 7. aprīlī noteikumiem Nr. 163)
<b>Poland - Occupational Exposure Limits</b>	
Local name	Propan
NDS (OEL TWA)	1800 mg/m <sup>3</sup>
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Romania - Occupational Exposure Limits</b>	
Local name	Propan
OEL TWA	1400 mg/m <sup>3</sup>
	778 ppm
OEL STEL	1800 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
<b>Slovenia - Occupational Exposure Limits</b>	
Local name	propan
OEL TWA	1800 mg/m <sup>3</sup>
	1000 ppm
OEL STEL	7200 mg/m <sup>3</sup>
	4000 ppm
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
<b>Spain - Occupational Exposure Limits</b>	
Local name	Propano
VLA-ED (OEL TWA)	1000 ppm Hidrocarburos alifáticos alcanos (C1 – C4) y sus mezclas, gases (Butano; Etano; Metano; Propano)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
<b>Iceland - Occupational Exposure Limits</b>	
Local name	Própan (flöskugas)
OEL TWA	1800 mg/m <sup>3</sup>
	1000 ppm

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



propane (74-98-6)	
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
<b>Norway - Occupational Exposure Limits</b>	
Local name	Propan
Grenseverdi (OEL TWA)	900 mg/m <sup>3</sup>
	500 ppm
Regulatory reference	FOR-2021-06-28-2248
<b>North Macedonia - Occupational Exposure Limits</b>	
Local name	Пропан
OEL TWA	1800 mg/m <sup>3</sup>
	1000 ppm
KTV	4
Short time value [mg/m <sup>3</sup> ]	7200 mg/m <sup>3</sup>
Short time value [ppm]	4000 ppm
Remark	(KTV) краткотрајна вредност (KTV) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m <sup>3</sup> или во ml/m <sup>3</sup> (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	Propane / Propan
MAK (OEL TWA)	1800 mg/m <sup>3</sup>
	1000 ppm
KZGW (OEL STEL)	7200 mg/m <sup>3</sup>
	4000 ppm
Critical toxicity	Formel / Formal
Remark	NIOSH

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Regulatory reference	www.suva.ch, 28.03.2022
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Propane
Remark (ACGIH)	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2022

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### Personal protective equipment:

Personal protective equipment symbol(s):



### 8.2.2.1. Eye and face protection

#### Eye protection:

Safety glasses

### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Impermeable protective gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0.35		EN ISO 374

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### 8.2.2.4. Thermal hazards

No additional information available

## 8.2.3. Environmental exposure controls

### Environmental exposure controls:

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Not available
Odour	:	Not available
Odour threshold	:	Not available
Melting point	:	Not applicable
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Extremely flammable aerosol.
Explosive properties	:	Pressurised container: May burst if heated.
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	41 °C
Auto-ignition temperature	:	Not available
Decomposition temperature	:	> °C
pH	:	Not available
Viscosity, kinematic	:	Not available
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	0,815 g/ml
Relative density	:	Not available
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 73 %

#### 9.2.2. Other safety characteristics

Relative evaporation rate (ethanol=1) : <  
VOC content : 74 % 495.8g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.



# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



## 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

## 10.5. Incompatible materials

No additional information available.

## 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
 Acute toxicity (dermal) : Not classified  
 Acute toxicity (inhalation) : Not classified

2-butoxyethanol (111-76-2)	
LD50 oral rat	1746 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 oral	1414 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Guinea pig, Male / female, Experimental value, Oral, 14 day(s))

butane (106-97-8)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value of similar product, Inhalation (gases))
propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

Skin corrosion/irritation : Not classified

2-butoxyethanol (111-76-2)	
pH	No data available in the literature
butane (106-97-8)	
pH	No data available in the literature
propane (74-98-6)	
pH	No data available in the literature

Serious eye damage/irritation : Not classified

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



2-butoxyethanol (111-76-2)	
pH	No data available in the literature
butane (106-97-8)	
pH	No data available in the literature
propane (74-98-6)	
pH	No data available in the literature

Respiratory or skin sensitisation : Not classified  
 Germ cell mutagenicity : Not classified  
 Carcinogenicity : Not classified  
 Reproductive toxicity : Not classified  
 STOT-single exposure : Not classified

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

2-butoxyethanol (111-76-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard : May be fatal if swallowed and enters airways

VROOAM MPL Multipurpose Lubricant	
Vaporizer	Aerosol
2-butoxyethanol (111-76-2)	
Viscosity, kinematic	3,642 mm <sup>2</sup> /s (20 °C, Not relevant)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	
Viscosity, kinematic	1,35 mm <sup>2</sup> /s
butane (106-97-8)	
Viscosity, kinematic	No data available in the literature

propane (74-98-6)	
Viscosity, kinematic	No data available in the literature

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



## 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology – general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

2-butoxyethanol (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 - Other aquatic organisms [1]	1550 mg/l waterflea
EC50 - Other aquatic organisms [2]	911 mg/l
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
butane (106-97-8)	
LC50 - Fish [1]	24,11 mg/l (ECOSAR, 96 h, Pisces, Fresh water, QSAR)
EC50 96h - Algae [1]	7,71 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)
propane (74-98-6)	
LC50 - Fish [1]	50 mg/l (96 h, Pisces, Fresh water, QSAR, Estimated value)
EC50 96h - Algae [1]	12 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

### 12.2. Persistence and degradability

2-butoxyethanol (111-76-2)	
Persistence and degradability	Readily biodegradable in water.
butane (106-97-8)	
Persistence and degradability	Readily biodegradable in water.

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



<b>propane (74-98-6)</b>	
Persistence and degradability	Readily biodegradable in water.

## 12.3. Bioaccumulative potential

<b>2-butoxyethanol (111-76-2)</b>	
Partition coefficient n-octanol/water (Log Pow)	0,81 (Experimental value, BASF test, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>butane (106-97-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	2,8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>propane (74-98-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	1,1 – 2,8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

## 12.4. Mobility in soil

<b>2-butoxyethanol (111-76-2)</b>	
Surface tension	65,03 mN/m (20 °C, 2 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0,5 – 0,9 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
<b>butane (106-97-8)</b>	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).
<b>propane (74-98-6)</b>	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).

## 12.5. Results of PBT and vPvB assessment

<b>Component</b>	
2-butoxyethanol (111-76-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



butane (106-97-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

## 12.6. Other adverse effects

No additional information available

## 12.7. Other adverse effects

No additional information available






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

## RUBRIEK 14: Informatie met betrekking tot het vervoer

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1950	UN 1950	UN 1950	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1 (61°C c.c.)	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

## 14.6. Special precautions for user

### Overland transport

Classification code (ADR)	:	5F
Special provisions (ADR)	:	190, 327, 344, 625
Limited quantities (ADR)	:	1I
Excepted quantities (ADR)	:	E0
Packing instructions (ADR)	:	P207, LP200
Special packing provisions (ADR)	:	PP87, RR6, L2
Mixed packing provisions (ADR)	:	MP9
Transport category (ADR)	:	2
Special provisions for carriage - Packages (ADR)	:	V14
Special provisions for carriage - Loading, unloading and handling (ADR)	:	CV9, CV12
Special provisions for carriage - Operation (ADR)	:	S2
Tunnel restriction code (ADR)	:	D

### Transport by sea

Special provisions (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	:	SP277
Excepted quantities (IMDG)	:	E0
Packing instructions (IMDG)	:	P207, LP200
Special packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D
EmS-No. (Spillage)	:	S-U
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

### Air transport

PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provisions (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L

### Inland waterway transport

Classification code (ADN)	:	5F
Special provisions (ADN)	:	190, 327, 344, 625
Limited quantities (ADN)	:	1 L
Excepted quantities (ADN)	:	E0
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01, VE04
Number of blue cones/lights (ADN)	:	1

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



## Rail transport

Classification code (RID)	:	5F
Special provisions (RID)	:	190, 327, 344, 625
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E0
Packing instructions (RID)	:	P207, LP200
Special packing provisions (RID)	:	PP87, RR6, L2
Mixed packing provisions (RID)	:	MP9
Transport category (RID)	:	2
Special provisions for carriage – Packages (RID)	:	W14
Special provisions for carriage - Loading, unloading and handling (RID)	:	CW9, CW12
Colis express (express parcels) (RID)	:	CE2
Hazard identification number (RID)	:	23

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### VOC Directive (2004/42)

VOC content : 74 % 495.8g/l

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



## 15.1.2. National regulations

### France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamide; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

### Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

### Netherlands

- ABM category : B(2) - toxic for aquatic organisms
- SZW-lijst van kankerverwekkende stoffen : None of the components are listed
- SZW-lijst van mutagene stoffen : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

### Denmark

- Class for fire hazard : Class II-1
- Store unit : 5 liter
- Classification remarks : R10 <H222;H229;H336>; Emergency management guidelines for the storage of flammable liquids must be followed
- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

### Switzerland

- Storage class (LK) : LK 2 - Liquefied or pressurized gases

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
-----	---



# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
STOT SE 3	H336	Calculation method

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM MPL MULTIPURPOSE LUBRICANT



SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental

requirements only. It should not therefore be construed as guaranteeing any specific property of the product.