

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name : VROOAM PTFE Spray 0,4l  
Product code : 63925

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture: Lubricant

### 1.3. Details of the supplier of the safety data sheet

VROOAM Powersports Lubricants INT. B.V.  
Aventurijn 300  
3316 LB Dordrecht (NL)  
0031 (0) 78 750 1632  
[www.vrooam-lubricants.com](http://www.vrooam-lubricants.com)  
[info@vrooam-lubricants.com](mailto:info@vrooam-lubricants.com)

· Further information obtainable from: Product Safety Department

1.4. Emergency telephone number: 0031 (0) 78 750 16 32 (9 AM to 5 PM, Monday to Friday)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008



GHS02 flame

Aerosol 1 : H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2 : H315 Causes skin irritation.  
STOT SE 3 : H336 May cause drowsiness or dizziness.  
Asp. Tox. 1 : H304 May be fatal if swallowed and enters airways.  
Aquatic Chronic 3 : H412 Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms (CLP) :



GHS02



GHS07

Signal word (CLP) : Danger

**Hazard-determining components of labelling:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Pentane

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



Hazard statements (CLP) : H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P273 Avoid release to the environment.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P403 Store in a well-ventilated place.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/ regional/ national/ international regulations.

## 2.3. Other hazards

### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Description: Active substance with propellant

### 3.2. Mixtures

Dangerous components		
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 92128-66-0 EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	2.5-<10%
CAS: 109-66-0 EINECS: 203-692-4 Reg.nr.: 01-2119459286-30	Pentane Flam. Liq. 1, H224; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	2.5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	1-<2.5%

Additional information:

## SECTION 4: First aid measures

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



## 4.1. Description of first aid measures

After inhalation : Supply fresh air; consult doctor in case of complaints.  
 After skin contact : Generally the product does not irritate the skin.  
 After eye contact : Rinse opened eye for several minutes under running water.  
 After swallowing : Do not induce vomiting; call for medical help immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

## 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing agents : Water haze  
 Fire-extinguishing powder  
 Carbon dioxide  
 Alcohol resistant foam

For safety reasons unsuitable extinguishing agents: Water with full jet

### 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

### 5.3 Advice for firefighters

Protective equipment: Mount respiratory protective device.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

### 6.2. Environmental precautions

Do not allow product to reach sewage system or any water course.  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.

### 6.3. Methods and material for containment and cleaning up

Ensure adequate ventilation.  
 Do not flush with water or aqueous cleansing agents

### 6.4. Reference to other sections

See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

## SECTION 7: Handling and storage

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



## 7.1. Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

### Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles : Store in a cool location.

: Observe official regulations on storing packagings with pressurised containers.

### Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

### Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

## 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

### 8.1. Control parameters

Ingredients with limit values that require monitoring at the workplace:		
<b>106-97-8 butane (containing &lt; 0.1% butadiene (203-450-8))</b>		
WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	
<b>109-66-0 Pentane</b>		
WEL	Long-term value: 1800 mg/m <sup>3</sup> , 600 ppm	
<b>74-98-6 propane</b>		
WEL	Long-term value: 1800 mg/m <sup>3</sup>	
<b>75-28-5 isobutane (containing &lt; 0,1 % butadiene (203-450-8))</b>		
WEL	Short-term value: 2400 mg/m <sup>3</sup> Long-term value: 1900 mg/m <sup>3</sup>	
DNELs		
<b>92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>		
Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer) 773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m <sup>3</sup> (Consumer) 2035 mg/m <sup>3</sup> (Worker)
<b>109-66-0 Pentane</b>		
Oral	DNEL Long term-systemic	214 mg/kg bw/day (Consumer)

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



Dermal	DNEL Long term-systemic	214 mg/kg bw/day (Consumer) 432 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	643 mg/m3 (Consumer) 3000 mg/m3 (Worker)

**Additional information:** The lists valid during the making were used as basis.

## 8.2. Exposure controls

### Personal protective equipment:

#### General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

#### Respiratory protection:

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

#### Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\leq 0.5$  mm

#### Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye protection:

Safety glasses



Tightly sealed goggles

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



Body protection: Use protective suit. (EN-13034/6)

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### General Information

##### Appearance:

Form : Aerosol  
Colour : According to product specification

Odour : characteristic.  
Odour threshold : Not determined.  
pH -value : Not determined

##### Change in condition:

Melting point : Undetermined  
Initial boiling point and boiling range : -44.5 °C

Flash point : -97 °C  
Flammability (solid, gas) : Not applicable.  
Auto-ignition temperature : Product is not self igniting.  
Explosive properties : Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.  
Not determined.

##### Explosion limits:

Lower : 0.8 Vol %  
Upper : 10.9 Vol %

Vapour pressure at 20 °C : 3000 hPa  
Density at 20 °C : 0.735 g/cm<sup>3</sup>  
Relative density : Not determined.  
Vapour density : Not determined.  
Evaporation rate : Not applicable.

##### Solubility in / Miscibility with

Water : Not miscible or difficult to mix.

Partition coefficient: n-octanol/water : Not determined.

##### Viscosity:

Dynamic : Not determined.  
Kinematic : Not determined.

##### Solvent content:

Organic solvents : 40.4 %  
Solids content : 5.6 %

### 9.2 Other information

No further relevant information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



No further relevant information available

## 10.2. Chemical stability

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

## 10.3. Possibility of hazardous reactions

No dangerous reactions known.

## 10.4. Conditions to avoid

No further relevant information available.

## 10.5. Incompatible materials

No further relevant information available.

## 10.6. Hazardous decomposition products

No dangerous decomposition products known.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Acute toxicity** : Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rabbit)
Inhalative	LC50/4h	>25 mg/l (rat)

#### Primary irritant effect:

Skin corrosion/irritation : Causes skin irritation.  
 Serious eye damage/irritation : Based on available data, the classification criteria are not met.  
 Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):

Germ cell mutagenicity : Based on available data, the classification criteria are not met.  
 Carcinogenicity : Based on available data, the classification criteria are not met.  
 Reproductive toxicity : Based on available data, the classification criteria are not met.  
 STOT-single exposure : May cause drowsiness or dizziness.  
 STOT-repeated exposure : Based on available data, the classification criteria are not met.  
 Aspiration hazard : May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1 Toxicity

· Aquatic toxicity:

92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
NOELR (72h)	3 mg/l (Pseudokirchneriella subcapitata)
EL50(48h)	3 mg/l (Daphnia magna)
EL50 (72h)	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	11.4 mg/l (Oncorhynchus mykiss (96h))
NOEC (21 days)	0.17 mg/l (Daphnia magna)
LOEC (21 days)	0.32 mg/l (Daphnia magna)
109-66-0 Pentane	

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



NOEC (72h)	7.51 mg/l (Pseudokirchneriella subcapitata)
EC50 (72h)	10.7 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	4.26 mg/l (Oncorhynchus mykiss (96h))
EC50/48h	2.7 mg/l (Daphnia magna)

## 12.2 Persistence and degradability

No further relevant information available.

## 12.3 Bioaccumulative potential

No further relevant information available.

## 12.4 Mobility in soil

No further relevant information available.

Ecotoxic effects:

Remark

: Harmful to fish

Additional ecological information:

General notes

: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

## 12.5 Results of PBT and vPvB assessment

PBT

: Not applicable.

vPvB

: Not applicable.

## 12.6 Other adverse effects

No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Recommendation

: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
HP3	Flammable
HP14	Ecotoxic

Uncleaned packaging:

Recommendation

: Disposal must be made according to official regulations.



## RUBRIEK 14: Informatie met betrekking tot het vervoer



# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



<b>14.1 UN-Number</b>	
ADR, ADN, IMDG, IATA	: UN1950
<b>14.2 UN proper shipping name</b>	
ADR, ADN	: UN1950 AEROSOLS
IMDG	: AEROSOLS
IATA	: AEROSOLS, flammable
<b>14.3 Transport hazard class(es)</b>	
<b>ADR</b>	
	
Class	: 2 5F Gases.
Label	: 2.1
<b>ADN</b>	
ADN/R Class	: 2 5F
<b>IMDG, IATA</b>	
	
Class	: 2.1
Label	: 2.1
<b>14.4 Packing group</b>	
ADR, IMDG, IATA	: Void
<b>14.5 Environmental hazards:</b>	
Marine pollutant	: No
<b>14.6 Special precautions for user</b>	
Warning	: Gases.
Danger code (Kemler)	: -
- EMS Number	: F-D, S-U
	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	: SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2..
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	
Not applicable.	
Transport/Additional information:	
ADR	
Limited quantities (LQ)	: 1L
Excepted quantities (EQ) Code	: E0
	Not permitted as Excepted Quantity
Transport category	: 2

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



Tunnel restriction code	: D
IMDG	
Limited quantities (LQ)	: 1L
Excepted quantities (EQ) Code	: E0
	Not permitted as Excepted Quantity
UN "Model Regulation"	: UN 1950 AEROSOLS, 2.1

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

#### Seveso category

P3a FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

#### National regulations:

Class	Share in %
NK	25-<50

VOC-CH 40.40 %

VOC-EU 296.9 g/l

Danish MAL Code 5-3

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapour.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Research & Development

Contact: VROOAM Lubricants

#### Abbreviations and acronyms:

RID	: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
-----	--

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM PTFE SPRAY 0,4l



ICAO	: International Civil Aviation Organisation
ADR	: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG	: International Maritime Code for Dangerous Goods
IATA	: International Air Transport Association
GHS	: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS	: European Inventory of Existing Commercial Chemical Substances
ELINCS	: European List of Notified Chemical Substances
CAS	: Chemical Abstracts Service (division of the American Chemical Society)
MAL-Code	: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
DNEL	: Derived No-Effect Level (REACH)
LC50	: Lethal concentration, 50 percent
LD50	: Lethal dose, 50 percent
PBT	: Persistent, Bioaccumulative and Toxic
vPvB	: very Persistent and very Bioaccumulative
Flam. Gas 1	: Flammable gases – Category 1
Aerosol 1	: Aerosols – Category 1
Press. Gas (Comp.)	: Gases under pressure – Compressed gas
Flam. Liq. 1	: Flammable liquids – Category 1
Flam. Liq. 2	: Flammable liquids – Category 2
Skin Irrit. 2	: Skin corrosion/irritation – Category 2
STOT SE 3	: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1	: Aspiration hazard – Category 1
Aquatic Chronic 2	: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3	: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

\* Data compared to the previous version altered. \*