

SAFETY DATA SHEET

PRODUCT NAME: VROOAM POWER WAX+ 0,4L



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : VROOAM POWER WAX+ 0,4L
Product code : 63935

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture: Lubricant

1.3. Details of the supplier of the safety data sheet

VROOAM Powersports Lubricants INT. B.V.
Aventurijn 300
3316 LB Dordrecht (NL)
0031 (0) 78 750 1632
www.vrooam-lubricants.com
info@vrooam-lubricants.com

· Further information obtainable from: Product Safety Department

1.4. Emergency telephone number: 0031 (0) 78 750 16 32 (9 AM to 5 PM, Monday to Friday)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008



GHS02 flame

Aerosol 1 : H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) : Danger

Hazard-determining components of labelling: Hydrocarbons, C10-C13,n-alkanes, cyclic, <2%aromates, Benzene <0.1% (R)-p-mentha-1,8-diene. Terpinolene. Lemongras oil.

Hazard statements (CLP) : H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Precautionary statements (CLP) : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.

SAFETY DATA SHEET

PRODUCT NAME: VROOAM POWER WAX+ 0,4l



P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves / eye protection.
 P301+P310 IF SWALLOWED: Immediately call a doctor.
 P331 Do NOT induce vomiting.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P403 Store in a well-ventilated place.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/ regional/ national/ international regulations.

Additional information : EUH208 Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

2.3. Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.1. Substances

Description: Active substance with propellant

3.2. Mixtures

Dangerous components		
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 1174522-09-8 EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1% Asp. Tox. 1, H304	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	1-<2.5%
CAS: 5989-27-5 EINECS: 227-813-5 Reg.nr.: 01-2119529223-47	(R)-p-mentha-1,8-diene Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.1- <0.25%

Ingredients according to detergents guideline 648/2004/EC	
aliphatic hydrocarbons	≥30%
non-ionic surfactants, phosphates, perfumes, (R)-p-mentha-1,8-diene	<5%

Additional information:

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation : Supply fresh air; consult doctor in case of complaints.
 After skin contact : Generally the product does not irritate the skin.
 After eye contact : Rinse opened eye for several minutes under running water.
 After swallowing : Do not induce vomiting; call for medical help immediately.

SAFETY DATA SHEET

PRODUCT NAME: VROOAM POWER WAX+ 0,4l



4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing agents : Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2. Environmental precautions

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

6.3. Methods and material for containment and cleaning up

Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

6.4. Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

SAFETY DATA SHEET

PRODUCT NAME: VROOAM POWER WAX+ 0,4I



7.2. Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles : Store in a cool location.
: Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1. Control parameters

Ingredients with limit values that require monitoring at the workplace:	
106-97-8 butane (containing < 0.1% butadiene (203-450-8))	
WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
1174522-09-8 Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1%	
OEL	Short-term value: 1200 mg/m ³ , 184 ppm
74-98-6 propane	
WEL	Long-term value: 1800 mg/m ³
75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8))	
WEL	Short-term value: 2400 mg/m ³ Long-term value: 1900 mg/m ³

Additional information: The lists valid during the making were used as basis.

8.2. Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

Respiratory protection:

Filter AX/P2
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A2/P2

Protection of hands:



Protective gloves

Solvent resistant gloves

SAFETY DATA SHEET

PRODUCT NAME: VROOAM POWER WAX+ 0,4I



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Safety glasses



Tightly sealed goggles

Body protection: Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Information

Appearance:

Form : Aerosol
Colour : According to product specification

Odour : characteristic.
Odour threshold : Not determined.
pH -value : Not determined

Change in condition:

Melting point : Undetermined
Initial boiling point and boiling range : -44.5 °C

Flash point : -97 °C
Flammability (solid, gas) : Not applicable.
Auto-ignition temperature : Product is not self igniting.
Explosive properties : Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
Not determined.

Explosion limits:

Lower : 0.7 Vol %

SAFETY DATA SHEET

PRODUCT NAME: VROOAM POWER WAX+ 0,4l



Upper	: 10.9 Vol %
Vapour pressure at 20 °C	: 3100 hPa
Density at 20 °C	: 0.842 g/cm ³
Relative density	: Not determined.
Vapour density	: Not determined.
Evaporation rate	: Not applicable.
Solubility in / Miscibility with	
Water	: Not miscible or difficult to mix.
Partition coefficient: n-octanol/water	: Not determined.
Viscosity:	
Dynamic	: Not determined.
Kinematic	: Not determined.
Solvent content:	
Organic solvents	: 32.1 %
Water	: 65.8 %
Solids content	: 1.1 %

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available

10.2. Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

SAFETY DATA SHEET

PRODUCT NAME: VROOAM POWER WAX+ 0,4I



1174522-09-8 Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1%		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4h	>4951 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation : Causes skin irritation.
 Serious eye damage/irritation : Based on available data, the classification criteria are not met.
 Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):

Germ cell mutagenicity : Based on available data, the classification criteria are not met.
 Carcinogenicity : Based on available data, the classification criteria are not met.
 Reproductive toxicity : Based on available data, the classification criteria are not met.
 STOT-single exposure : Based on available data, the classification criteria are not met.
 STOT-repeated exposure : Based on available data, the classification criteria are not met.
 Aspiration hazard : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

1174522-09-8 Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1%	
ELO (48h)	1000 mg/l (Daphnia magna)
ELO(72h)	1000 mg/l (Pseudokirchneriella subcapitata)
LL0(96h)	1000 mg/l (Oncorhynchus mykiss (96h))

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Ecotoxicological effects:

Remark : Harmful to fish

Additional ecological information:

General notes : Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
 Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.
 vPvB : Not applicable.

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation : Must not be disposed together with household garbage. Do not allow product to reach sewage system.

SAFETY DATA SHEET



PRODUCT NAME: VROOAM POWER WAX+ 0,4l



European waste catalogue	
HP3	Flammable

Uncleaned packaging:
 Recommendation : Disposal must be made according to official regulations.

RUBRIEK 14: Informatie met betrekking tot het vervoer

14.1 UN-Number	ADR, ADN, IMDG, IATA	: UN1950
14.2 UN proper shipping name	ADR, ADN IMDG IATA	: UN1950 AEROSOLS : AEROSOLS : AEROSOLS, flammable
14.3 Transport hazard class(es)	ADR	
		
	Class	: 2.1
	Label	: 2.1
	ADN	
	ADN/R Class	: 2.1
	IMDG, IATA	
		
	Class	: 2.1
	Label	: 2.1
14.4 Packing group	ADR, IMDG, IATA	: Void
14.5 Environmental hazards:	Marine pollutant	: No

SAFETY DATA SHEET

PRODUCT NAME: VROOAM POWER WAX+ 0,4l



14.6 Special precautions for user

Warning	: Gases.
Danger code (Kemler)	: -
· EMS Number	: F-D, S-U
	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	: SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

Transport/Additional information:

ADR	
Limited quantities (LQ)	: 1L
Excepted quantities (EQ) Code	: E0
	Not permitted as Excepted Quantity
Transport category	: 2
Tunnel restriction code	: D
IMDG	
Limited quantities (LQ)	: 1L
Excepted quantities (EQ) Code	: E0
	Not permitted as Excepted Quantity
UN "Model Regulation"	: UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P3a FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

Class	Share in %
Wasser	50-<75
NK	25-<50

VOC-CH 91.00 %

VOC-EU 270.6 g/l

Danish MAL Code 1-1

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SAFETY DATA SHEET

PRODUCT NAME: VROOAM POWER WAX+ 0,4I



SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Department issuing SDS: Research & Development

Contact: VROOAM Lubricants

Abbreviations and acronyms:

RID	: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR:	: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO	: International Civil Aviation Organisation
ICAO-TI	: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR	: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG	: International Maritime Code for Dangerous Goods
IATA	: International Air Transport Association
GHS	: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS	: European Inventory of Existing Commercial Chemical Substances
ELINCS	: European List of Notified Chemical Substances
CAS	: Chemical Abstracts Service (division of the American Chemical Society)
MAL-Code	: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
LC50	: Lethal concentration, 50 percent
LD50	: Lethal dose, 50 percent
PBT	: Persistent, Bioaccumulative and Toxic
vPvB	: very Persistent and very Bioaccumulative
Flam. Gas 1	: Flammable gases – Category 1
Aerosol 1	: Aerosols – Category 1
Press. Gas (Comp.)	: Gases under pressure – Compressed gas
Flam. Liq. 3	: Flammable liquids – Category 3
Skin Irrit. 2	: Skin sensitisation – Category 1
Skin Sens. 1	: Aspiration hazard – Category 1
Asp. Tox. 1	: Aspiration hazard – Category 1
Aquatic Acute 1:	: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1	: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

* Data compared to the previous version altered. *