

# SAFETY DATA SHEET



**PRODUCT NAME:** VROOAM VR70 FULLY SYNTHETIC ESTER BLEND 4T MOTORCYCLE ENGINE OIL 15W-50

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Trade name : VROOAM VR70 Fully Synthetic Ester Blend 4T Motorcycle Engine Oil 15W-50  
Product code : 64644  
Type of product : Lubricants  
Product group : Trade product

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use  
Use of the substance/mixture : Engine oil

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet.

VROOAM Powersports Lubricants INT. B.V.  
Aventurijn 300  
3316 LB Dordrecht (NL)  
0031 (0) 78 750 1632  
[www.vrooam-lubricants.com](http://www.vrooam-lubricants.com)  
[info@vrooam-lubricants.com](mailto:info@vrooam-lubricants.com)

· Further information obtainable from: Product Safety Department

**1.4. Emergency telephone number:** 0031 (0) 78 750 16 32 (9 AM to 5 PM, Monday to Friday)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**  
Not classified

#### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

### 2.2. Label elements

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**  
EUH-statements : EUH210 - Safety data sheet available on request.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# SAFETY DATA SHEET



PRODUCT NAME: VROOAM VR70 FULLY SYNTHETIC ESTER BLEND 4T MOTORCYCLE ENGINE OIL 15W-50

## 3.2. Mixtures

Comments : Highly refined mineral oils and additives.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Amines, polyethylenepoly-, reaction products with 1,3-dioxolan-2-one and succinic anhydride monopolyisobutenyl derivs	(CAS-No.) 147880-09-9 (EC-No.) 604-611-9	1 - 2,5	Aquatic Chronic 4, H413
bis(nonylphenyl)amine	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	0,1 - 2,5	Aquatic Chronic 4, H413

Comments : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346  
Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).  
 First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
 First-aid measures after skin contact : Wash skin with plenty of water.  
 First-aid measures after eye contact : Rinse eyes with water as a precaution.  
 First-aid measures after ingestion : Do not induce vomiting. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : No additional information available. Not expected to present a significant hazard under anticipated conditions of normal use.  
 Symptoms/effects after ingestion : May result in aspiration into the lungs, causing chemical pneumonia.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
 Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.  
 Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR70 FULLY SYNTHETIC ESTER BLEND 4T MOTORCYCLE ENGINE OIL 15W-50



## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep in a cool, well-ventilated place away from heat.

Storage temperature : 0 - 40 °C

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

VROOAM VR70 Fully Synthetic Ester Blend 4t Motorcycle Engine Oil 15W-50	
EU	Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended: 5 mg/m <sup>3</sup> - ACGIH TLV (inhalable fraction).

### 8.2. Exposure controls

Appropriate engineering controls:  
Ensure good ventilation of the work station.

Materials for protective clothing:
Wear suitable protective clothing

Hand protection:
Protective gloves

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR70 FULLY SYNTHETIC ESTER BLEND 4T MOTORCYCLE ENGINE OIL  
15W-50



Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	5 (> 240 minutes), 6 (> 480 minutes)	>=0,35		EN ISO 374

<b>Eye protection:</b>
Safety glasses

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

<b>Skin and body protection:</b>
Wear suitable protective clothing

<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



**Environmental exposure controls:**  
Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 238 °C - ASTM D92 (COC)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,855 kg/l (15 °C) - ASTM D4052
Solubility	: Water : Insoluble / Slightly miscible
Log Pow	: No data available
Viscosity, kinematic	: 114 mm <sup>2</sup> /s (40 °C) - ASTM D7279
Viscosity, dynamic	: No data available

# SAFETY DATA SHEET



**PRODUCT NAME:** VROOAM VR70 FULLY SYNTHETIC ESTER BLEND 4T MOTORCYCLE ENGINE OIL 15W-50

Explosive properties : Presents no particular fire or explosion hazard.  
 Oxidising properties : No data available  
 Explosive limits : No data available

## 9.2. Other information

VOC content : 0 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reacts violently with (strong) oxidizers.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available.

### 10.6. Hazardous decomposition products

No decomposition if stored normally.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
 Acute toxicity (dermal) : Not classified  
 Acute toxicity (inhalation) : Not classified

<b>bis(nonylphenyl)amine (36878-20-3)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)

Skin corrosion/irritation : Not classified  
 Serious eye damage/irritation : Not classified  
 Respiratory or skin sensitisation : Not classified  
 Germ cell mutagenicity : Not classified  
 Carcinogenicity : Not classified  
 Reproductive toxicity : Not classified  
 STOT-single exposure : Not classified  
 STOT-repeated exposure : Not classified  
 Aspiration hazard : Not classified

<b>VROOAM VR70 Fully Synthetic Ester Blend 4t Motorcycle Engine Oil 15W-50</b>	
Viscosity, kinematic	114 mm <sup>2</sup> /s (40 °C) - ASTM D7279

# SAFETY DATA SHEET

PRODUCT NAME: VROOAM VR70 FULLY SYNTHETIC ESTER BLEND 4T MOTORCYCLE ENGINE OIL  
15W-50



## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

bis(nonylphenyl)amine (36878-20-3)	
LC50 fish 1	> 100 mg/l Brachydanio rerio (zebra-fish)
EC50 Daphnia 1	> 100 mg/l (OECD 202 method)
EC50 72h algae (1)	600 mg/l
EC50 96h algae (1)	870 mg/l

### 12.2. Persistence and degradability

bis(nonylphenyl)amine (36878-20-3)	
Biodegradation	1 % (test concentration 20,1 mg/l)

### 12.3. Bioaccumulative potential

No additional information available.

### 12.4. Mobility in soil

No additional information available.

### 12.5. Results of PBT and vPvB assessment

No additional information available.

### 12.6. Other adverse effects

No additional information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

European List of Waste (LoW) code : 13 02 05\* - mineral-based non-chlorinated engine, gear and lubricating oils

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				

# SAFETY DATA SHEET



**PRODUCT NAME:** VROOAM VR70 FULLY SYNTHETIC ESTER BLEND 4T MOTORCYCLE ENGINE OIL 15W-50

Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

No supplementary information available

#### 14.6. Special precautions for user

Overland transport	: Not applicable
Transport by sea	: Not applicable
Air transport	: Not applicable
Inland waterway transport	: Not applicable
Rail transport	: Not applicable

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

VOC content : 0 %

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Comments
3	Composition/information on ingredients	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor

# SAFETY DATA SHEET



PRODUCT NAME: VROOAM VR70 FULLY SYNTHETIC ESTER BLEND 4T MOTORCYCLE ENGINE OIL  
15W-50

CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:	
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
H413	May cause long lasting harmful effects to aquatic life.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.