



AMERICAN V-TWIN

MINERAL MONOGRADE MOTORCYCLE ENGINE OIL 50

DESCRIPTION

This "old-fashion, old-school and hard-core" V-Twin single-grade 4-Stroke engine oil, provide performance and protection to meet the demands of (older) V-Twin air and water-cooled engines. This product will make the engine run smoother at high temperatures and will and prevents better against engine oil leaking through its high and stable viscosity.

APPLICATION:

This product can only be used in the engine and not in transmission and primary chaincase.

PERFORMANCE:

Viscosity: SAE 50.

Performance level: API SG/CF.

TYPICALS

Density at 15 °C, kg/l	0,897
Viscosity 40 °C, mm ² /s	206,00
Viscosity 100 °C, mm ² /s	19,40
Viscosity Index	107
Flashpoint, COC, °C	255
Pour Point, °C	-15
Total Base Number, mg KOH/g	6,9

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.