

AMERICAN V-TWIN PREMIUM MINERAL MOTORCYCLE ENGINE OIL 20W-50

DESCRIPTION

Custom formulated mineral 4-Stroke V-Twin motorcycle engine oil. This product provides shear, oxidation stability and deposit control for quality lubrication performance and engine protection. VROOAM's unique Performance Additive Technology means high viscosity index, less oil consumption, oxidation stability. Engines last longer and are more reliable with added wear protection to increase bearing life.

APPLICATION:

This is an excellent V-Twin engine oil for service departments, shop- and service fill, topping off and for new and rebuilt engine break-in for V-twin motorcycles. Equally suitable for air or liquid cooled V-Twin engines.

PERFORMANCE:

Viscosity: SAE 20W-50. Performance level: API SL; JASO MA/MA2.

TYPICALS

Density at 15 °C, kg/l	0,878
Viscosity 40 °C, mm²/s	169,00
Viscosity 100 °C, mm²/s	19,55
Viscosity Index	133
Flashpoint, COC, °C	234
Pour Point, °C	-33
Total Base Number, mg KOH/g	7,7

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM[®] LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.

VROOAM LUBRICANTS INTERNATIONAL

Aventurijn 300 3316 LB Dordrecht The Netherlands t, +31 (0) 78 750 16 32 e. info@vrooam-lubricants.com w. vrooam-lubricants.com