



VROOAM FORK OIL 5W

DESCRIPTION:

This oil for front forks is based on carefully selected base oils, to which a number of additives are added in order to obtain the following properties:

- High and stable viscosity index
- Excellent abrasion preventing properties
- Very good corrosion preventing properties
- Very good anti-foam and de-aerating properties
- Neutral towards synthetic seals
- Low pour point

FEATURES:

This fork oil is a high-performance fluid for optimum damping performance in all road and off-road suspensions. Developed for optimal absorption at all temperatures and provides easier sliding and avoid drag in the fork. Protects against foaming, corrosion and offers outstanding lubricity for smoother and safer braking. Provides superior anti-fade damping performance over a wide temperature range. Protection of seal end elastomer compatibility.

PERFORMANCE:

Specification: SAE 5W.

VROOAM® recommends this product for motorcycle forks that requires a SAE 5W fork oil.

TYPICALS:

Density at 15 °C, kg/l	0,877
Viscosity 20 °C, mm ² /s	49,60
Viscosity 40 °C, mm ² /s	22,50
Viscosity 100 °C, mm ² /s	5,07
Viscosity Index	162
Flashpoint, COC, °C	174
Pour Point, °C	-513

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.