



VROOAM KART 4T

SYNTHETIC ENGINE OIL 10W-40

DESCRIPTION:

A 4-stroke Synthetic engine oil. For use in high-quality 4-stroke kart engines with centrifugal clutch or integrated gearbox with wet clutch. Provides superior engine protection at high speeds and under heavy load. With smooth operation of gearbox and clutch.

PERFORMANCE:

Viscosity and performance levels: SAE 10W-40 API SM; JASO MA2.

TYPICALS:

Density at 15 °C, kg/l	0,853
Viscosity -25 °C, mPa.s	3370
Viscosity 40 °C, mm ² /s	83,60
Viscosity 100 °C, mm ² /s	13,60
Viscosity Index	163
Flashpoint, COC, °C	236
Pour Point, °C	-33
Total Base Number, mg KOH/g	7,6

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM[®] LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.