



VROOAM SCOOTER 2T

SYNTHETIC BLEND 2T SCOOTER ENGINE OIL

DESCRIPTION

A Synthetic blend 2-stroke scooter engine oil. For scooter riders who demand superior quality and performance combined with superior engine protection and cleanliness for their 2-stroke scooter engine. Suitable for OIL-INJECTION and PREMIX SYSTEMS.

APPLICATION:

This two stroke engine oil is advised for the lubrication of high speed aircooled two stroke engines under heavy duty load. This selfmixing two stroke engine oil may also be used for water cooled two stroke engines (radiator type cooling systems).

PERFORMANCE:

Minimum specifications: API TC | JASO FD | ISO-L-EGD.

VROOAM recommends this product for motorcycles and scooters that require the following specifications: API TC | JASO FD/FC/FB | ISO-L-EGD/EGC/EGB | Global GD | Husqvarna 272 | 2-Stroke DFI.

TYPICALS

Density at 15 °C, kg/l	0,875
Viscosity 40 °C, mm ² /s	64,60
Viscosity 100 °C, mm ² /s	9,50
Viscosity Index	129
Flashpoint, COC, °C	116
Total Base Number, mg KOH/g	1,4

RECOMMENDATIONS:

PREMIX: Mixing ratio as specified by the engine manufacturer
Mixing ratio in normal conditions 1:50 (2%)

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefullness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.