



VROOAM TRANSMISSION HYPOID OIL 80W-90

DESCRIPTION:

Mineral hypoid gear oil for separate gearboxes that require hypoid GL-5 gear oil. Excellent for noisy gearboxes, provides high oil film resistance even under the most severe conditions.

APPLICATION:

A mineral hypoid gear oil for all gearboxes without wet clutches & hypoid rear axles without LSD. Not recommended to use in gearboxes with wet clutches.

PERFORMANCE:

Viscosity and performance level: SAE 80W-90; API GL-5.

VROOAM® recommends this product for motorcycle transmissions that require the following specifications: SAE 80W-90; API GL-5

TYPICALS:

Density at 15 °C, kg/l	0,900
Viscosity 40 °C, mm²/s	149,00
Viscosity 100 °C, mm²/s	14,80
Viscosity Index	98
Flashpoint, COC, °Cx	232
Pour Point, °C	-30
Acid number, mgKOH/g	1,80
Sulphate Ash, %	0,05

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.