



VROOAM TRANSMISSION OIL SCOOTER 75W-90

DESCRIPTION:

Synthetic based Scooter transmission oil, developed for use in scooter transmissions. Provides a superior protection at high temperatures with an easy start and shifting when cold. Offers extreme pressure lubricating protection, easy and smooth transmission operation at racing and city driving conditions.

PERFORMANCE:

Viscosity and performance levels: SAE 75W-90; API GL-4, API GL-5.

VROOAM® recommends this product for scooter transmissions that require the following specifications: SAE 75W-90; API GL-4, API GL-5.

TYPICALS:

Density at 15 °C, kg/l	0,878
Viscosity 40 °C, mm²/s	84,60
Viscosity 100 °C, mm²/s	15,00
Viscosity Index	187
Flashpoint, COC, °Cx	182
Pour Point, °C	-48

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefullness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.