



VROOAM VR4

SYNTHETIC 2T ENGINE OIL

DESCRIPTION

A Synthetic 2-stroke engine oil that meets the highest specifications and classifications. For 2-stroke motorcycles for road and off-road use. Excellent engine protection, keeps the engine clean, produces less smoke and prevents deposit formation. Suitable for OIL-INJECTION and PREMIX SYSTEMS.

APPLICATION:

For performance air and water cooled 2-stroke engines, including tuned moto-cross and other 2-stroke performance engines. Lubricant is suitable for oil injector systems or premix, standard leaded and unleaded gasoline.

PERFORMANCE:

Minimum specifications: API TC | JASO FD | ISO-L-EGD.

VROOAM recommends this product for motorcycles and scooters that require the following specifications: API TC | JASO FD/FC/FB | ISO-L-EGD/EGC/EGB; Husqvarna; Piaggio Hexagon.

TYPICALS

Density at 15 °C, kg/l	0,878
Viscosity 40 °C, mm ² /s	70,50
Viscosity 100 °C, mm ² /s	11,00
Viscosity Index	147
Flashpoint, COC, °C	78
Total Base Number, mg KOH/g	2,9

RECOMMENDATIONS:

PREMIX: Mixing ratio as specified by the engine manufacturer
Mixing ratio in normal conditions 1:50 (2%)

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.