



VROOAM VR50 10W-40

SYNTHETIC ESTER BLEND 4T MOTORCYCLE ENGINE OIL

ESTER+ FORMULA

APPLICATION:

For performance air and water-cooled 4-stroke motorcycle and scooter engines. Including sports-, touring-, street-, off road-, enduro- and trial bikes with integrated or non-integrated gearbox, wet or dry clutch. For use in all conditions, roads, city and off-road. Easy and secure shifting at low and high temperatures. This product is the most sold VROOAM product and successfully used as workshop oil by the largest motorcycle dealership in The Netherlands.

FEATURES:

- Provides ultimate engine protection, including smooth clutch and gearbox operation.
- Quick engine response and improved power output and increased reliability.
- High lubricating properties.
- High viscosity index.
- Keeps the engine clean.
- Anti-wear additives.

PERFORMANCE:

Viscosity and performance levels: SAE 10W-40; API SM; JASO MA2.

VROOAM® recommends this product for motorcycle engines that require the following specifications and classifications: API SM/SL/SJ/SH/SG/SF; JASO MA/MA2.

TYPICALS:

Density at 15 °C, kg/l	0,852
Viscosity 40 °C, mm ² /s	81,60
Viscosity 100 °C, mm ² /s	13,40
Viscosity Index	167
Flashpoint, COC, °C	235
Total Base Number, mg KOH/g	7,6

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.