



# VROOAM VR6

## 100% SYNTHETIC 2T ENGINE OIL

### DESCRIPTION

100% synthetic 2-stroke motorcycle engine oil meets highest specifications and classifications. For high-performance, high-RPM 2-stroke engines. Ultimate throttle response and increased power output and increased reliability all at the same time. For all premix 2-stroke engines with a mixing ratio as specified by the manufacturer. Suitable for OIL-INJECTION and PREMIX SYSTEMS.

### APPLICATION:

For performance air and water cooled 2-stroke engines, including tuned motocross and other 2-stroke performance engines. Lubricant is suitable for oil injector systems or premix, standard leaded and unleaded gasoline.

### PERFORMANCE:

Minimum specifications: API TC | JASO FD | ISO-L-EGD.

VROOAM recommends this product for motorcycles and scooters that require the following specifications: API TC | JASO FD/FC/FB.

### TYPICALS

Colour	Light Yellow
Density at 15 °C, kg/l	0,875
Viscosity 40 °C, mm <sup>2</sup> /s	44,00
Viscosity 100 °C, mm <sup>2</sup> /s	8,64
Viscosity Index	179
Flashpoint, COC, °C	80
Total Base Number, mg KOH/g	6,7

### RECOMMENDATIONS:

**PREMIX:** Mixing ratio as specified by the engine manufacturer  
Mixing ratio racing conditions: from 1:33 to 1:25 (3% to 4%),  
Mixing ratio in normal conditions 1:50 (2%)

**MADE IN THE NETHERLANDS**

#### PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.