



# VROOAM VR70 15W-50

## FULLY SYNTHETIC ESTER BLEND 4T MOTORCYCLE ENGINE OIL

### MULTI ESTER FORMULA

#### APPLICATION:

A fully synthetic 4-stroke motorcycle engine oil that meets highest specifications and classifications. For High Performance air and water-cooled 4-stroke motorcycle and scooter engines, including sports-, touring-, street-, off road-, enduro- and trial bikes with integrated or non-integrated gearbox, wet or dry clutch. For use in all conditions; roads, city and off-road. Easy and secure shifting at low and high temperatures.

#### FEATURES:

- Provides ultimate engine protection including smooth clutch and gearbox operation.
- Quick engine response and improved power output and increased reliability.
- High lubricating properties.
- High viscosity index.
- Keeps the engine clean.
- Anti-wear additives.

#### PERFORMANCE:

**Viscosity and performance levels:** SAE 15W-50; API SN; JASO MA2.

**VROOAM® recommends this product for performance motorcycles that require the following specifications and classifications:** API SN/SM/SL/SJ/SH/SG/SF; JASO MA/MA2.

#### TYPICALS:

Density at 15 °C, kg/l	0,854
Viscosity 40 °C, mm <sup>2</sup> /s	114,00
Viscosity 100 °C, mm <sup>2</sup> /s	17,10
Viscosity Index	164
Flashpoint, COC, °C	240
Total Base Number, MGKOH/G	8,0

**MADE IN THE NETHERLANDS**

#### PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.