

MARINE GEAR LUBE 90

MINERAL MARINE GEAR OIL FOR TRANSMISSIONS AND OUTBOARD LOWER UNITS.

APPLICATION:

This gear oil should be used in marine hypoid differentials and gearboxes for which an EP-transmission oil is advised.

PERFORMANCE:

Viscosity and Specification: SAE 90; API GL4

DESCRIPTION:

This gear oil is a mineral lubricating oil for mechanical transmissions, formulated with high-quality solvent refined base oils and special EP-additives to obtain the following properties:

- Good resistance against oxidation
- Good rust-preventing, anti-corrosion and foam inhibiting properties
- Low pourpoint
- Good Extreme Pressure (EP) properties

TYPICALS:

Density at 15 °C, kg/l	0,895	
Viscosity 40 °C, mm²/s	191,00	
Viscosity 100 °C, mm²/s	16,50	
Viscosity Index	96	
Flash Point COC, °C	230	
Pour Point, °C	-15	

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the

stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.