



MR4 25-40

MARINE 4T OUTBOARD ENGINE OIL

APPLICATION:

This 4-Stroke engine oil is special advised for the lubrication of high speed four stroke engines under heavy duty load. MR4 25W-40 meets the latest requirement for outboard engines set by the NMMA.

DESCRIPTION:

4-Stroke engine oil for outboard application and formulated to achieve the following properties:

- Perfect lubrication
- High detergency
- Good cold start properties
- Strong against wear, oxidation and corrosion properties
- High shear stability

PERFORMANCE:

Viscosity and Specification: SAE 25W-40; NMMA FC-W

TYPICALS:

Density at 15 °C, kg/l	0,870
Viscosity 40 °C, mm ² /s	139,00
Viscosity 100 °C, mm ² /s	14,50
Viscosity Index	103
Flash Point COC, °C	240
Pour Point, °C	-25

MADE IN THE NETHERLANDS

PSYCHICAL PRODUCT CHARACTERISTICS ON REQUEST

With continual research and development, VROOAM® LUBRICANTS, retain the right to modify the information of our products in order to offer our customers the latest technical development. The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.